

# Hand-Held Label Applicators

**Ideal for applying pressure-sensitive labels and RFID tags**

Weber's line of manual label applicators provides an easy, productive means of hand-held labeling. Available in three separate sizes to address various label widths, the units can be used to apply pressure-sensitive labels from 20mm to 100mm in width.

And for pre-encoded RFID tags, the units have been specially designed to apply the tags without damaging the RFID inlays.

These handy applicators employ an exclusive label edge detector that automatically senses the leading edge of the label to ensure accurate dispensing. In addition, all three applicators can dispense any type of label or RFID tag without the use of a special liner tool, cartridge or cassette.

Unlike other manual methods of label application, our units include these unique features:

- Simple side loading minimizes label threading time
- Exclusive edge detector eliminates the need for liner slits or perforations
- Positive feed roller provides accurate dispensing

## It's easy to use our hand-held applicators

1. Remove label guide by turning it clockwise, then place the roll of labels or RFID tags onto the spool. Replace guide by pressing inward and turning it counterclockwise.
2. Pull label under the transparent pressure plate. Open the bottom gate, release the latch marked "Open" and thread label edge along the bottom gate.
3. Close the bottom gate by returning the "Open" latch to its original locked position. Use the serrated edge to remove excess label liner.
4. Labels are released upon squeezing the handle. During squeezing, pull the applicator smoothly along the surface of the package/product being labeled.
5. To clear or clean the unit, remove two screws to free Mecha-Sensor and use solvent for adhesive removal.

Note: It is unnecessary to slit label liner in order to feed labels; for use with die-cut labels only, remove excess adhesive with a cotton swab moistened with alcohol.

## Specifications

Model	Label Depth	Label Width	Max. Outer Diameter
AP65-30	20-60mm	20-30mm	100mm
AP65-60	20-60mm	25-60mm	100mm
AP65-100	20-60mm	55-100mm	100mm

## Applicator Selection Guide

Model	Roll OD	Core ID	Max Label Width	Min Label Width	Max Label Repeat	Min Label Repeat	Die-Cut
AP65-30	88.9mm (3.5")	25.4mm (1.0")	28.575mm (1.125")	20mm (0.8125")	63.5mm (2.5")	6.35mm (0.25")	Yes
AP65-60	88.9mm (3.5")	25.4mm (1.0")	57.15mm (2.25")	25mm (0.9375")	63.5mm (2.5")	6.35mm (0.25")	Yes
AP65-100	88.9mm (3.5")	25.4mm (1.0")	98.425mm (3.875")	55mm (2.165")	63.5mm (2.5")	6.35mm (0.25")	Yes

Note: OD is the outer dimension of the label roll; ID is the inner dimension of the label core; Label Repeat is the distance between labels on the liner.



# Weber®

LABELS & LABELING SOLUTIONS

**Weber Marking Systems, Inc.**

711 West Algonquin Rd. • Arlington Heights, IL 60005-4457  
847.364.8500 • FAX 847.364.8575

[www.webermarking.com](http://www.webermarking.com)